

Adheseal

Product: Everbond P.V.A. Plastabond

S.D.S No.1052

Date: 19/11/2007

Page: 1 of 3

MATERIAL SAFETY DATA SHEET

SUPPLIER: ADHESEAL

EMERGENCY TELEPHONE

NUMBER: 07 3560000

ADDRESS: 2 / 8 HARVTON ST
STAFFORD 4053

PRODUCT NAME: P.V.A. Plastabond **PRODUCT TYPE:** PVA ADHESIVE

HAZARD INFORMATION: UN number N/A HAZCHEM Coding N/A
UN Hazard Class: N/A

APPEARANCE: Viscous opaque/white liquid **PACKING:** 4lt
20lt
200lt

COMPOSITION: Water, polyvinyl acetate, dibutyl phthalate (less than 5%), vinyl acetate monomer
(less than 5%)

ACTIVE CONSTITUENTS: Polyvinyl acetate

Adheseal

PAGE 2

Product: P.V.A. Plastabond

PROPERTIES: Opaque viscous liquid with slight acetic odour. Specific Gravity (20oC) 1.08-1.10.
Mildly corrosive to steel, brass and zinc alloys

FLAMMABILITY: Non-flammable as supplied. Material is combustible after evaporation of water, producing carbon dioxide gases.

PRECAUTIONS IN HANDLING: No special precautions. Normal good industrial and personal hygiene should be employed. Avoid contact with eyes, skin and mouth.

HEALTH: Eye liable to cause pain and redness.

HAZARDS:

SKIN: Not regarded as a hazard. Repeated prolonged exposure may lead to skin dryness, with possible dermatitis in certain individuals

INDIGESTION: Considered harmful if swallowed.

INHALATION: Not regarded as an inhalation hazard.

STORAGE PRECAUTIONS: Store in a cool place. Keep containers closed when not in use.

TRANSPORT PRECAUTIONS: No special precautions.

Adheseal

PAGE 3

Product: P.V.A. Plastabond

SPILL AND LEAK PROCEDURES: Spills should be contained, absorbed on sand or earth and sealed in a plastic or steel container for disposal. Do not allow to enter drains as clogging may occur.

Spills and small leaks should be hosed down with excess water. Untreated will form permanent films on floor and other surfaces.

WASTE DISPOSAL: Minor quantities absorbent sand or earth may be disposed of in industrial wastes. For major quantities refer to local Waste Disposal Authorities.

ADDITIONAL COMMENTS: Contaminated clothing, rags and other fabrics will rapidly become stiff and unusable due to setting of the adhesive on the fibres.

Prepared by: MG Johnson

Date: 19/11/2007