



5056 GRADE

**TRUSS HEAD DOME HEAD**  
**LARGE FLANGE RIVETS** HEADSIZE = 2.5 TIMES RIVET DIAMETER

ALUMINIUM / STEEL

Part No	Body	Mandrel	Body Dia. mm	Grip Range mm	Recommended mm	Body Length mm	Clearance mm	Head Dia. mm	Shear (N)	Tensile (N)	Inner Qty	Outer Qty
73ASL42	Aluminium	Steel	3.2 (1/8)	1.6-3.2	3.3	6.85	9.1	10.05	760	980	1000	10000
73ASL44	Aluminium	Steel	3.2 (1/8)	4.8-6.4	3.3	9.95	12.2	10.05	760	980	1000	10000
73ASL46	Aluminium	Steel	3.2 (1/8)	7.9-9.5	3.3	13.45	15.7	10.05	760	980	1000	10000
73ASL48	Aluminium	Steel	3.2 (1/8)	9.5-12.7	3.3	16.85	19.1	10.05	760	980	500	5000
73ASL54	Aluminium	Steel	4.0 (5/32)	4.8-6.4	4.1	10.55	13.3	12.7	1160	1560	500	5000
73ASL56	Aluminium	Steel	4.0 (5/32)	7.9-9.5	4.1	13.75	16.5	12.7	1160	1560	500	5000
73ASL63	Aluminium	Steel	4.8 (3/16)	3.2-4.8	4.9	9.65	12.65	16.5	1690	2220	250	2500
73ASL64	Aluminium	Steel	4.8 (3/16)	4.8-6.4	4.9	11.25	14.25	16.5	1690	2220	250	2500
73ASL66	Aluminium	Steel	4.8 (3/16)	7.9-9.5	4.9	14.45	17.45	16.5	1690	2220	250	2500
73ASL68	Aluminium	Steel	4.8 (3/16)	9.5-12.7	4.9	17.55	20.55	16.5	1690	2220	250	2500
73ASL610	Aluminium	Steel	4.8 (3/16)	12.7-15.9	4.9	21.45	24.45	16.5	1690	2220	250	2500
73ASL612	Aluminium	Steel	4.8 (3/16)	15.9-19	4.9	24.65	27.65	16.5	1690	2220	250	2500
73ASL614	Aluminium	Steel	4.8 (3/16)	19-22.2	4.9	27.95	30.95	16.5	1690	2220	250	2500
73ASL616	Aluminium	Steel	4.8 (3/16)	22.2-25.4	4.9	31.25	34.25	16.5	1690	2220	250	2500

LARGE FLANGE ALUMINIUM - STEEL

The Aluminium / Steel **Large Flange Truss Head** range is made from 5056 aluminium alloy wire with a low carbon content, zinc plated, steel mandrel, to suit those applications where soft or composite materials such as timber, plastic or fibreglass, are being fixed to sheet or plate metal. Manufactured by Spurway Cooke in Singapore, using only the highest quality wire available, you can be assured of the highest consistency and quality.

