



1010 GRADE
TRUSS HEAD DOME HEAD
STEEL

STEEL / STEEL

Part No	Body	Mandrel	Body Dia. mm	Grip Range mm	Recommended mm	Body Length mm	Clearance mm	Head Dia. mm	Shear (N)	Tensile (N)	Inner Qty	Outer Qty
73SS42	Steel	Steel	3.2 (1/8)	1.6-3.2	3.3	6.85	9.1	6.65	1160	1380	1000	10000
73SS43	Steel	Steel	3.2 (1/8)	3.2-4.8	3.3	8.35	10.6	6.65	1160	1380	1000	10000
73SS44	Steel	Steel	3.2 (1/8)	4.8-6.4	3.3	9.95	12.2	6.65	1160	1380	1000	10000
73SS45	Steel	Steel	3.2 (1/8)	6.4-7.9	3.3	11.55	13.8	6.65	1160	1380	1000	10000
73SS46	Steel	Steel	3.2 (1/8)	7.9-9.5	3.3	13.45	15.7	6.65	1160	1380	1000	10000
73SS48	Steel	Steel	3.2 (1/8)	9.5-12.7	3.3	16.85	19.1	6.65	1160	1380	1000	10000
73SS52	Steel	Steel	4.0 (5/32)	1.6-3.2	4.1	7.45	10.2	8.45	1650	2090	1000	10000
73SS53	Steel	Steel	4.0 (5/32)	3.2-4.8	4.1	9.05	11.8	8.45	1650	2090	1000	10000
73SS54	Steel	Steel	4.0 (5/32)	4.8-6.4	4.1	10.55	13.3	8.45	1650	2090	1000	10000
73SS55	Steel	Steel	4.0 (5/32)	6.4-7.9	4.1	12.05	14.8	8.45	1650	2090	1000	10000
73SS56	Steel	Steel	4.0 (5/32)	7.9-9.5	4.1	13.75	16.5	8.45	1650	2090	500	5000
73SS58	Steel	Steel	4.0 (5/32)	9.5-12.7	4.1	17.45	20.2	8.45	1650	2090	500	5000
73SS61	Steel	Steel	4.8 (3/16)	Up to 1.6	4.9	6.45	9.45	10	2400	3020	500	5000
73SS62	Steel	Steel	4.8 (3/16)	1.6-3.2	4.9	8.05	11.05	10	2400	3020	500	5000
73SS63	Steel	Steel	4.8 (3/16)	3.2-4.8	4.9	9.65	12.65	10	2400	3020	500	5000
73SS64	Steel	Steel	4.8 (3/16)	4.8-6.4	4.9	11.25	14.25	10	2400	3020	500	5000
73SS65	Steel	Steel	4.8 (3/16)	6.4-7.9	4.9	12.85	15.85	10	2400	3020	500	5000
73SS66	Steel	Steel	4.8 (3/16)	7.9-9.5	4.9	14.45	17.45	10	2400	3020	500	5000
73SS68	Steel	Steel	4.8 (3/16)	9.5-12.7	4.9	17.55	20.55	10	2400	3020	500	5000
73SS610	Steel	Steel	4.8 (3/16)	12.7-15.9	4.9	21.45	24.45	10	2400	3020	500	5000
73SS612	Steel	Steel	4.8 (3/16)	15.9-19	4.9	24.65	27.65	10	2400	3020	250	2500
73SS82	Steel	Steel	6.4 (1/4)	1.6-3.2	6.5	8.75	12.5	13.05	4450	5520	250	2500
73SS84	Steel	Steel	6.4 (1/4)	4.8-6.4	6.5	12.6	16.35	13.05	4450	5520	250	2500
73SS86	Steel	Steel	6.4 (1/4)	7.9-9.5	6.5	15.8	19.55	13.05	4450	5520	250	2500
73SS88	Steel	Steel	6.4 (1/4)	9.5-12.7	6.5	19	22.75	13.05	4450	5520	250	2500

The Steel / Steel Truss Head range is made from 1010 grade low carbon steel wire with a low carbon content, zinc plated, steel mandrel to suit those applications where the joint is comprised of all steel materials such as steel house frames. Manufactured by Spurway Cooke in Singapore, using only the highest quality wire available, you can be assured of the highest consistency and quality.

