



HIGH GRADE
COUNTERSUNK HEAD FLAT HEAD
MONEL

60% NICKEL 40% COPPER / STEEL

Part No	Body	Mandrel	Body Dia. mm	Grip Range mm	Recommended mm	Body Length mm	Clearance mm	Head Dia. mm	Shear (N)	Tensile (N)	Inner Qty	Outer Qty
72MS42	NI/CU	Steel	3.2 (1/8)	1.6-3.2	3.3	6.85	9.1	5.9	1560	2000	1000	10000
72MS44	NI/CU	Steel	3.2 (1/8)	4.8-6.4	3.3	9.95	12.2	5.9	1560	2000	1000	10000
72MS54	NI/CU	Steel	4.0 (5/32)	4.8-6.4	4.1	10.55	13.3	7.4	2450	3110	1000	10000
72MS64	NI/CU	Steel	4.8 (3/16)	4.8-6.4	4.9	11.25	14.25	8.9	3200	4450	500	5000
72MS66	NI/CU	Steel	4.8 (3/16)	7.9-9.5	4.9	14.45	17.45	8.9	3200	4450	500	5000



The **Monel / Steel Countersunk Head** range is made from heading quality 400HQ grade Monel wire with a medium carbon content, zinc plated, steel mandrel to suit those applications where high tensile strengths, corrosion resistance and a flush finish is required. Manufactured by Spurway Cooke in Singapore, using only the highest quality wire consisting of 60%Nickel and 40% copper, you can be assured of the highest consistency and quality. This range is commonly used where Stainless Steel is not suitable as it has similar corrosion resistance and tensile strengths.