

AR-011MX AR-011HX

Expand your opportunities when using blind rivets.

The worldwide standard in this series, the Lobster Pneumatic Riveter AR-011

A masterful evolution - 50 years in the making!

The legacy model AR-011 now features new improvements.
Introducing the redesigned model!!



Pneumatic Riveter AR-011MX • AR-011HX



Launched in 1967 and following a long line of success in the field, features redesigned improvements.

information



- Durable! A main feature of the AR-011 is its durability.
- Increase in stroke! The MX series will increase from 14mm (0.55") to 16mm (0.63") in stroke length.(14%up!)
- Capable of pulling Stainless rivets! With the Ultra Jaws and **Soft-Set** function, will allow the MX/HX series to set Stainless rivets.
- Improves maintenance...Applying one-touch detachable Jaw Case, its maintenance has become easier.
- Lower noise level. The standard silencer function will improve overall working environment.
- Improved operating performance. The new Rotary Joint and soft safety cover will improve usage by the operator.
- Customization. Optional parts will expand capabilities and operator usage.

Option



Short Trigger Straight Joint

Model	Weight (kg)	Stroke (mm)	Traction Power (kN)	Compatible Rivets ϕ mm (inch)	Air Consumption (L/pcs)	Noise Emission (dB)	Used Air Pressure (MPa)
AR011MX	1.5	16	9	2.4(3/32") ~4.8(3/16")	1.8	75	0.5~0.6
AR011HX	2.1	16.5	14	2.4(3/32") ~6.4(1/4")	2.4	75	0.5~0.6

※**Soft-Set** is the name of LOBSTER shock-less function which will reduce the riveting impact with the operator making it operator friendly in the workplace.

Pneumatic Riveter R1A1 • R1A2



information



- Lightest in class. (R1A1)
- Long Stroke (R1A1 : 19 mm (0.75"), R1A2 : 26 mm (1.02"))
- Eco Type with reduced air consumption
- High performance. High power model which is capable to work with high strength rivets. (R1A2)
- **Soft-Set** (Shock-less function) will decrease the impact of riveting.
- Air supply port can be relocated to the left or right side of the tool.
- Easy to access vacuum ON/OFF switch.

Model	Weight (kg)	Stroke (mm)	Traction Power (kN)	Compatible Rivets ϕ mm (inch)	Air Consumption (L/pcs)	Noise Emission (dB)	Used Air Pressure (MPa)
R1A1	1.1	19	10.0	2.4(3/32") ~4.8(3/16")	68	69.5	0.5~0.6
R1A2	1.74	26	18.5	4.8(3/16") ~6.4(1/4")*	75	80	0.5~0.6

※When working S-Bolt of LOBSTER, optional parts will be required.



Cordless Riveter R1B1 • R1B2



information




- Compact body of the class (cordless riveter).
- High speed riveting.
- Handle design to reduce the fatigue of the worker.
- Will be able to work 560 pcs of 4.8 mm (3/16") stainless blind rivets with one charge. (When using 1.5Ah battery pack)
- Oversized Mandrel Collector
- Light up the working piece with the LED light

Model	Weight (kg)	Stroke (mm)	Traction Power (kN)	Compatible Rivets ϕ mm (inch)	Battery Pack		
					Types	Electrical Voltage	Capacity
R1B1	1.9	22	10.5	2.4(3/32") ~4.8(3/16")	Li-ion	DC14.4V	1.5Ah
R1B2	2.0	22	13.0	4.8(3/16") ~6.4(1/4")*			

※3.2 mm (1/8") and 4.0 mm (5/32") rivets can be used if optional parts are attached.

※When working S-Bolt of LOBSTER, optional parts will be required.

※Stainless rivets 6.4 mm (1/4") cannot be used.



⚠ Caution for secure usage

Be sure to read enclosed Instruction Manual carefully and make sure that you understand them thoroughly before using this tool.

●All dimensions are nominal and subject to tolerances.

●Specification are subject to change without prior notice.



ABN 23 068 361 455
PO Box 2225, Logan City DC Qld 4114
Website: www.aerofast.com.au
Email: lobster@aerofast.com.au



LOBTEX CO.,LTD.

International Marketing Group

BRISBANE
8 Booran Drive
Woodridge Qld 4114
Ph: (07) 3299 4555

GOLD COAST
1/13 John Duncan Court
Varsity Lakes Qld 4226
Ph: (07) 5593 4550

SUNSHINE COAST
2/34 Premier Circuit
Warana Qld 4575
Ph: (07) 5437 7737

12-8 Shijo-Cho, Higashi-Osaka City, Osaka 579-8053 Japan
URL : www.riveter.com www.lobtex.co.jp/